



## Envirotech PVC Free Mesh Fabric 300 FR B1 W/W

### FEATURES AND BENEFITS

- PVC free mesh material
- Fire rated to EN13501 certification
- Available in widths up to 3.2m
- Premium grade product

Suitable for use with:



Order Code	W (mm)	L (m)	Weight (gsm)
IST275323	3200	50	300



## Envirotech PVC Free Mesh Fabric 300 FR B1 W/W

### TECHNICAL SPECIFICATIONS

Properties	Test method	Result	Unit
Total Strength (W/F)	DIN 53354	200/166 1960/1627	Kg/5cm N/5cm
Total Resistance (W/F)	DIN 53363	37/30.0 362.6/294	Kg N
Temperature Resistance	DIN 53361	-40 ~ +90	°C
Max Width	DIN EN ISO 2286-1	3.2	Meter
Flame Retardant	NFPA-701, DIN4102-B1, NFP92-507 M2, Euroclass B-S1-D0	B1	
Environmental	EN-71, 33P, ROHS, REACH	REACH	

*NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.*