

# 201-OAPAE SERIES

## FLEXIBLE WHITE MATTE PVC - PERMANENT ADHESIVE

201-OAPAE Series (Air Egress) is a 85 mic premium matte white flexible polymeric vinyl film coated with 200-5031 permanent gray acrylic pressure sensitive adhesive laminated to a 135 gsm AE layflat liner. This film is designed to accept a variety of solvent-based, UV curable and latex inks common to wide format digital printing systems. Adhesive 200-5031 offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 135 gsm AE liner offers excellent product layflat in a variety of ambient conditions along with ease of application for large format graphics.

<b>Applications</b>	201-OAPAE Series is designed for large format interior or exterior signage, decals, nameplates and point-of-purchase displays.	
<b>Thickness</b>	Film	85 mic.
	Adhesive	25 mic
	Liner	135 gsm.
	(Thickness variance +/- 10%)	
<b>Dimensional Stability</b>	Good.	
<b>Temperature Ranges</b>	Minimum application temperature	+4,4°Celsius
	Service temperature	-40°C to +82°C.
<b>Expected Exposure</b>	Up to 3 years unprinted under normal exposure conditions.	
<b>Exterior</b>	Up to 5 years unprinted under normal exposure conditions	
<b>Interior</b>		
<b>Adhesion</b>	To stainless steel	10,94 N/25mm
Average bond	PSTC-101 Method A with 24 hr. dwell at 21°C and 50% relative humidity. Typical values. Individual values may vary. Test your application thoroughly.	
<b>Water Resistance</b>	Good. Test if immersed.	
<b>Humidity Resistance</b>	Good.	
<b>Solvent Resistance</b>	Good.	
<b>Storage Stability</b>	6-month shelf life when stored at 21°C and 50% relative humidity	
<b>Product Series</b>	1,37m x 50m	