

203 SERIESFLEXIBLE GLOSS WHITE PVC - PERMANENT ADHESIVE

203 Series is a 75 mic premium white gloss flexible calendared vinyl film coated with 200-5000 permanent acrylic pressure sensitive adhesive laminated to a 135 gsm layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. Adhesive 200-5000 produces permanent bond to a variety of common substrates used in the graphics industry. The 135 gsm liner offers excellent product layflat in a variety of environmental conditions.

Applications Concept®203 is designed for interior or exterior signage, decals, nameplates, and

point-ofpurchase displays.

Thickness Film 75 mic.

Adhesive 25 mic Liner 135 gsm.

(Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature +4,4°Celsius

Service temperature -40°C to +82°C.

Expected Exterior Exposure Up to 5 years.

Adhesion To stainless steel 10,94 N/25mm

PSTC-101 Method A with 24 hr. dwell at 21°C and 50% relative humidity. Typical

values. Individual values may vary. Test thoroughly for your specific use.

Water Resistance Good. Test if immersed.

Humidity Resistance Good.

Solvent Resistance Good.

Storage Stability 6-month shelf life when stored at 21°C and 50% relative humidity

Product Series 1,37m x 50m

1,52m x 50m

Recommendations Completely evaporate inkjet solvents before application. Failure to do so may

facilitate solvent penetration resulting in vinyl degradation.