

ASPHALT WALK® SMOOTH

AsphaltWalk® Smooth is designed for short to medium-term applications depending on where the product is applied. AsphaltWalk® Smooth is the perfect product for application on outdoor walls. It is very easy to remove and usually without any residues. The adhesive was specially designed for outdoor use.

Durability

Based on our experience we recommend a maximum use of 2 years.

Printing method

UV curable inks, solvent, ecosolvent and latex.

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

AsphaltWalk® Smooth is designed to be fully recyclable. Used material and production waste can be handled as "aluminum waste".



Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.

Uses

- Outdoor walls
- Building wraps
- Temporary building signage
- Sporting events

Features & Benefit

- Easy to apply and remove
- AsphaltWalk® smooth is fully recyclable
- Perfect adhesion on all surfaces
- PVC free



Distributed in the UK by:

INNOTECH

innotechdigital.com / 01530 512 731 / sales@innotechdigital.com

Technical Information

AsphaltWalk Smooth

Size	Width: 1.22 m Length: 30.48 m	
Material	Coated soft aluminum	75µ +/- 10µ
Adhesive	Permanent acrylic solvent	80µ +/- 5µ
Certificates	Flame resistance	M1 / F2
Application	Minimum application temperature	+10°C / +50°F

Peel Adhesion to	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	80oz/in (88N/100 mm)	50oz/in (55N/100mm)	70oz/in (77N/100mm)
24 hours dwell	100oz/in (110N/100 mm)	60oz/in (66N/100 mm)	80oz/in (88N/100 mm)

Chemical Resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	I	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion
 I = recommended for intermittent exposure only
 NR = not recommended

* Colour and lot variances of coated surfaces including paints, powder coatings, lacquers, stains and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface. **At temperatures below +10 °C the surface has to be pre-treated with a gas burner.

Distributed in the UK by:

INNOTECH

innotechdigital.com / 01530 512 731 / sales@innotechdigital.com