

MY FLOOR FILM & LAMINATE

MyFloor Film & Laminate is a classic floor film made of a calendered vinyl film with a gray back and an antislip laminate. MyFloor Film & Laminate is used at POS and can also be used indoors on nearly any surface.

Durability

Up to 6 months for indoor applications.

Printing method

UV curable inks, solvent, ecosolvent and latex.

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

It is recommended to handle the used material and production waste as industrial waste.

Warranty

Continental Gratrix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Gratrix materials found to not meet our product specifications. In no case shall Continental Gratrix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Gratrix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.



Uses

POS
Events
Reception area
Shopping center

Features & Benefit

Easy application and removal
Removal without adhesive residue
Excellent durability
Great heat resistance and dimensional stability
Good chemical resistance
Cleaning with machines guaranteed



Distributed in the UK by:

Technical Information		MyFloor Film
Size	Width: 1.372 m Length: 30.48 m	
Material	Glossy, self-adhesive vinyl film with printable white front Siliconized paper liner	100μ +/- 5μ 120g/m2
Adhesive	Grey permanent solvent adhesive	20g/m2 +/-3g/m2
Application	Minimum application temperature	+10°C / +50°F
Certificate	Flammability	B1

Technical Information		MyFloor Laminate
Size	Width: 1.372 m Length: 30.48 m	
Material	Embossed, anti-slip laminate	240μ +/- 5μ
Adhesive	Permanent solvent adhesive	20g/m2 +/-3g/m2
Certificate	Slip resistance	R10
	Fire Classification	DIN EN 13501-1

Distributed in the UK by:

INNOTECH

innotechdigital.com / 01530 512 731 / sales@innotechdigital.com