

107 SERIESPRINT MOUNTING FILM

107 Series Print Mounting Film is a double-coated pressure sensitive 40 mic opaque white polypropylene film with the 200-4985 permanent adhesive. One 115gsm white paper liner is used. This product is designed for laminating thin flexible films and papers under 254 mic in total thickness. This opaque mounting film is laminated by the cold laminating process without the addition of heat.

Applications Print Mounting Film is designed to mount photographic, digital, screen printed, and other

printed images to a variety of substrates such as Gatorfoam®, Fome-Cor®, and Sintra®. May also be used with smooth painted metal and clean plastic substrates such as ABS, rigid vinyl and styrene. In all cases the substrates must be clean and free of dust, dirt

and oil.

Thickness Film 40 mic.

Adhesive 25 mic Liner 115 gsm.

(Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature +4,4°Celsius

Service temperature -40°C to +82°C.

Adhesion To stainless steel 15,32 N/25mm

When tested according to PSTC-1 with 24 hr. dwell at 21°C and 50% relative humidity.

Typical values. Individual values may vary. Test thoroughly before production.

Opacity Approximately 93%

Storage Stability 1-year shelf life when stored at 21°C and 50% relative humidity.