

210 SERIESTRAFFIC GRAFFIC BASE VINYL REMOVABLE ADHESIVE

210 Series is a specially formulated flexible vinyl with a high performance acrylic pressure sensitive adhesive on a 135 gsm stayflat liner. The combination of vinyl and adhesive allows removability of the film from most common commercial tile floor substrates for up to 6 months under normal exposure conditions. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems.

Applications 210 Series is designed for temporary floor signs, decals, and point of purchase advertis-

ing. Overlamination is required to provide protection to the graphics. UL approved over-

laminates for slip resistance are 109 Series or 211 Series.

Thickness Film 85 mic.

Adhesive 25 mic Liner 135 gsm.

(Thickness variance +/- 10%)

Temperature Ranges Minimum application temperature +4,4°Celsius

Service Temperature -40°C to +82°C.

Adhesion To stainless steel 2,19 N/25mm

PSTC-1 with 24 hour dwell at 21°C and 50 % relative humidity. Typical values. Individ-

ual values may vary. Test thoroughly before production.

Removability Up to 6 months from most common commercial tile floors. Floor must be clean before

application. All tiles must be firmly attached to the sub floor. Painted floors must have excellent adhesion to the sub floor. Test all painted cement floors for adhesion of the

paint before applying a floor decal.

Water Resistance Good. Do not saturate

Humidity Resistance Excellent.

Solvent Resistance Excellent.

Storage Stability 6-months when stored at 21°C and 50% relative humidity.

Product Series 1,37m x 50m

Recommendations Completely evaporate inkjet solvents before application. Failure to do so may facili-

tate solvent penetration resulting in vinyl degradation.