

226 SERIESWALLMARK® WALL VINYL FILM

226 Series is a 150 mic premium white matte semi rigid calendared vinyl film with a specially formulated microsphere acrylic removable pressure sensitive adhesive backed by a 135 gsm layflat liner. The combination of vinyl and adhesive allows removability of this product from normal wall surfaces. The 135 gsm tight release digital liner provides excellent stability for processing using standard solvent and UV curable digital inks common to wide format digital printing systems.

Applications 226 Series is designed for temporary application of decals and graphics to most

types of painted interior walls and windows. This includes most flat, semi gloss and gloss paint finishes. Decals may also be applied to sealed wall coverings. The surface must be smooth and clean prior to application. If applying to new paint consult the paint manufacturer for proper drying conditions before 226 Series application. Not designed for coated/sealed/treated stainless steel, brass or bronze surfaces.

Thickness Film 150 mic.

Adhesive 25 mic Liner 135 gsm

(Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature +4,4°Celsius

Service temperature -40°C to +93°C.

Removability Removable up to 1 year under normal interior conditions.

Adhesion To glass 2,74 N/25mm

To standard test panels 2,74 N/25mm

Tested according to PSTC-101 Method A procedures with 24 hour dwell at 21°C and

50% relative humidity. Typical values. Individual values may vary. Bond to wall

surfaces may vary. Test thoroughly before production.

Water Resistance Limited immersion resistance. Test for specific application.

Humidity Resistance Good

Storage Stability 6 months shelf life when stored at 21°C and 50% relative humidity.

Product Series 1,37m x 30.48m

Recommendations Completely evaporate inkjet solvents before application. Failure to do so may facilitate

solvent penetration resulting in vinyl degradation.