

240 SERIES AUTOMARK® - MATTE OVERLAMINATING FILM

clear 200-5002 permanent acrylic adhesive on a bleached kraft 80 gsm over laminate liner. This vinyl film offers protection from ultra violet radiation, moisture and other environmental exposures. It is laminated by the cold laminating process without the addition of heat.

Applications	240 Series matte overlaminating vinyl film is designed to protect digital image prints and screen printed images for vehicle wraps and graphics, exhibit and display graphics. Can be used in most instances where an UV overlay with a matte finish is required. 240 series is recommended for use with 230 Series AutoMark wrap media.	
Thickness	Film Adhesive Liner (Thickness variance +/- 10%)	60 mic. 25 mic 80 gsm
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature Service temperature range	+4,4°Celsius -40°C to +82°C.
Expected Exterior Exposure	240 Series is a premium vinyl film that incorporated UV stabilizers in its formulation. Under normal exposure conditions up to 5 years resistance can be ex- pected.	
Adhesion	To stainless steel	10,94 N/25mm
	When tested according to PSTC-101 Method A with 24 hr. dwell at 21°C and 50% rela- tive humidity. Typical values. Individual values may vary. Test thoroughly before pro- duction.	
Light Transmission	Approximately 85%	
Gloss 60 Gardner	Initial ≤ 10	
Storage Stability	1-year shelf life when stored at 70°F and 50% relative humidity.	
Product Series	1,37mx50m 1,52m x 50m	