

Kinetix Standard Car Mag White Matt

FEATURES AND BENEFITS

- Durable magnetic sheet designed for use on vehicles.
- Intended for indoor and outdoor use
- Have holding strength at highway speeds.

Suitable for use with:



Order Code	W (mm)	L (mm)
INM100232	620	30

Kinetix Standard Car Mag White Matt

TECHNICAL SPECIFICATIONS

Properties	Result	Unit
Thickness	0.85	Mm
Pull	44~53	g/cm ²
Magnetic Properties—Br	1830	Gs
Magnetic Properties—HcB	1357	Oe
Magnetic Properties—HcJ	1888	Oe

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.