

PVC Double Sided Mesh Banner 380 FR B1

3800g/m2 PVC Mesh Blockout Banner without backing Liner.

FEATURES AND BENEFITS

- Suitable for indoor and outdoor use
- Available in 3.2m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm2)
ISB275403	2500	50	380

PVC Double Sided Mesh Banner 380 FR B1

TECHNICAL SPECIFICATIONS

Item	Method	Result		Unit
Weight of Fabric	DIN53352 BS3424 Method 5B	180±5		GSM
Weight of PVC	DIN53352 BS3424 Method 5B	200±5		GSM
Total weight	DIN53352 BS3424 Method 5A	380±10		GSM
Width		Up to 3.2		M
Breaking Strength	DIN53354 BS3424 Method 6A	Warp	2500	N/5cm
		Weft	1800	
Tearing Strength	DIN53356 BS3424 Method 7A	Warp	235	N/5cm
		Weft	220	
Temperature Resistance	DIN53357 BS3425 Method 10	-20-70		°C

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.