

PVC Mesh With Liner 400

270g/m² PVC Mesh Banner with a 130g/m² synthetic backing liner.

FEATURES AND BENEFITS

- Suitable for indoor and outdoor use
- Available in 3.2m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm ²)
ISB274042	1370	30	400
ISB274051	1600	30	400
ISB274555	1900	50	400
ISB274060	2500	50	400
ISB274957	3200	65	400

PVC Mesh With Liner 400

TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight		270	g/sq.m
Liner		130	g/sq.m
Tensile Strength (W/F)	DIN 53354	1200/1500	N/5cm
Tear Resistance (W/F)	DIN 53363	300/280	N/5cm
Welding Adhesion	DIN 53357	80	N/5cm
Temperature Resistance	DIN 53372	-20 - +70	°C
Air Loading	ISO 9237	2150	mm/s
Max Width	DIN EN ISO 2286-1	3.2	Meter
Flame Retardant	N/A		

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.