

PVC Mesh Without Liner 270 FR B1

270g/m2 PVC Mesh Banner without backing Liner, suitable for the largest banner applications

FEATURES AND BENEFITS

- Suitable for indoor and outdoor use
- Available in 3.2m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm2)
ISB275421	2200	50	270
ISB275310	3200	50	270
ISB275313	3200	65	270

PVC Mesh Without Liner 270 FR B1

TECHNICAL SPECIFICATIONS

Properties	Result	Unit	Test Method
Weight	270	gsm	
Film	PVC		
Base Fabric	Polyester		
Tensile Strength (L/W)	1350/1300	N/5cm	DIN53354
Tearing Strength (L/W)	300/250	N/5cm	DIN53363
Temperature Resistance	-30/+70	°C	DIN53372

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.