

Solvent Front Print Backlit - Display Film 210

A coated polyester which allows images to be illuminated from behind. It can be used for any back-light applications, including city lights and light boxes, as well as all displays and expo lighting systems. Excellent image quality, very good ink absorption, fantastic saturation and contrast.

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (ums)
ISB274636	1,100	30	210mic
ISB274639	1,270	30	210mic
ISB274642	1,524	30	210mic

Solvent Front Print Backlit - Display Film 210

Product Structure

Base material: 180 mic PET film
 Primer coating: 5 mic
 Ink receptive coating: 22 - 25 mic
 Total: 210 mic (+/- 3 mic)

	Unit	Value	Test Method
Thermal			
Heat	% MD	1.6	SKC Method
Shrinkage	% TD	0.7	(150 °C x 30min)
Durability	1 year (indoor durability, unprinted PVC)		

General Tips & Storage

After printing the ink must be perfectly dry so as to avoid any affect on the later combination with the application surface. The surface on which material is applied must be free of dust, grease, lubricant and any other substances which may hinder the film from adhesion. Freshly lacquered or painted surfaces should be allowed to dry for no less than three weeks. The compatibility of particular lacquers and paints should be tested by the user, prior to application on the material.

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.