

## Vertex Premium Adhesive Wall Fabric 340

Vertex Premium Adhesive Wall 340 is a self adhesive coated 100% polyester textile.

Designed for the interior design and retail industry, for wallpapers and temporary retail graphics.

Installation is a breeze and doesn't require experienced installers, due to its flexibility and canvas properties. It ensures that there are no bubbles to contend with while applying, and allows you to adapt to more irregular surfaces and corners.

Available in 1370mm and 1520mm widths and compatible with Eco-Solvent, Solvent, UV-C and Latex inks.

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gsm)
IST275146	1370	20	340
IST274972	1520	30	340

# Vertex Premium Adhesive Wall Fabric 340

## TECHNICAL SPECIFICATIONS

Properties	
Fabric Base	100% polyester textile - 230 g/m <sup>2</sup> and 240mic satin white coating
Adhesive	Acrylic UV hot melt, water and heat high resistance. 30 g/m <sup>2</sup>
Liner	Clay coated paper. 80 g/m <sup>2</sup>
Peel 180° Method FTM1 (n /25mm)	After 20 min.: max. 1.1N After 4 hours: max. 1.1N After 24 hours: max. 1.2N

*NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.*