

Vertex Texture Polyester Coated Fabric 300 FR B1, Bs1 d0, Class 0

Versatile 100% polyester textured textile at 300gsm for a wide range of applications including retail, hanging displays, exhibitions, canvas frames and wall paper.

FEATURES AND BENEFITS

- PVC Free material and 100% recyclable
- Fire rated to B1, Bs1 d0, and Class 0 certification.
- Available in widths up to 5m
- Premium grade product
- White back and grey back versions

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gsm)	
ISB275424	914	50	300	Grey back
IST274945	1370	50	300	White back
IST275170	1800	50	300	Grey back
IST274948	2200	50	300	White back
IST274951	3200	50	300	White back
IST275227	3200	50	300	Grey back
IST274954	5000	50	300	Grey back
IST275224	5000	50	300	White back
ISB275370	3200	50	310	Blue Back
ISB275289	3200	50	350	White Back

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.

Vertex Texture Polyester Coated Fabric 300 FR B1, Bs1 d0, Class 0

TECHNICAL SPECIFICATIONS

Properties	Test method	Result	Unit
Total Weight	DIN EN ISO 2286-2	300	g/sq.m
Total Strength (W/F)	DIN 53354	190/85 1863/834	Kg/5cm N/5cm
Total Resistance (W/F)	DIN 53363	24/9.7 235/95	Kg/5cm N/5cm
Welding Adhesion	DIN 53357		Kg
Temperature Resistance	DIN 53361	-30 ~ +70	C
Max Width	DIN EN ISO 2286-1	5.0	Meter
Flame Retardant	NFPA-701,DIN4102-B1, FR-M2	-	-
	EN 13501	B-s1, d0	
	BS 476 part 7	Class 0	
Environmental	EN-71, 6P, ROHS, REACH	-	-

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.