

Printable Floor Lino 1200gsm SR R10

FEATURES AND BENEFITS

The Vistaflex Printable Floor Lino 1200g/m² has a heavy duty PVC surface with a foam PVC back which is specially designed to prevent movement. The material is slip rated to R10 certification and available in 2.2m and 3.2m widths at 25m in length. It's printable with UV-C inks and is ideal for short term exhibitions and events!

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm ²)
ISB275669	2200	25	1200
ISB275672	3200	25	1200

Printable Floor Lino 1200gsm SR R10

TECHNICAL SPECIFICATIONS

Properties	Unit
Weight (gsm)	1500
Thickness (mm)	2.3
Tensile Strength (N/50mm) Warp	3055
Tensile Strength (N/50mm) Weft	3055
Tearing Strength (N/50mm) Warp	145
Tearing Strength (N/50mm) Weft	145
Peeling Strength (N/50mm)	110

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.