

Monomeric One-Piece Floor Vinyl 150mic

Features & Benefits

- One piece, durable floorgraphic vinyl, which means that no lamination is required.
- Very easy to install
- Slip rated to R10 certification due to its unique structure
- Highly durable, suitable for short term indoor use
- Removes without residue.
- Available in 1370mm x 25m rolls.

Technical Data

Property	Result
Thickness	150mic ±10% (foil without embossing)
Colour	Digital White
Finish	Super Hexagon
Adhesive Type	Waterbased semi permanent clear
Liner	135gsm Siliconised Kraft
Dimensional Stability MD	≤0.5mm—FINAT 14
Dimensional Stability CD	≤0.5mm—FINAT 14
Adhesive Strength	7±4N/25mm—FINAT TM 1, after 24 hours, adhered to stainless steel
Fire behaviour	Self extinguishing, adhered to stainless steel
Anti Slip Certification	R10/V; DIN 51130

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.