

TECHNICAL SPECIFICATIONS

VISTAMAX® 3080SL MONOMERIC PERMANENT CLEAR LAMINATE 80MIC

Features & Benefits

- 1 year durability
- Designed to protect printed graphics from UV radiation and scratches
- Applications: Indoor and short term outdoor signage, POP, wall and window graphics

Laminating

- Leave the inks to cure for between 24-48 hours before overlaminating. Latex inks can be laminated immediately.
- We recommend combining this as a laminate with other vinyls from the VistaMAX range
- The material should reach room temperature and a relative humidity of approx. 50% prior to laminating.
- Ensure the material is kept free of dust, dirt and static. We recommend using gloves when handling the material.

Application

- Suitable for application to flat or slightly curved surfaces
- This product is not designed for application to low energy surfaces
- It is the responsibility of the user to determine the suitability of the material for the application.
- Test the application with a small piece of the material prior to doing the full application

Storage

- We recommend storing the material in its original tube and wrapping when not in use.
- Material can be stored for up to 12 months when stored in the original packaging
- Store between 20°C and 25°C at 50% relative humidity

Characteristic	Result
Film Type	Transparent PVC film, 80mic
Liner Type	One side PE and silicon coated kraft paper 120gsm
Adhesive Type	Permanent clear solvent adhesive
Film Thickness	80mic
Total Thickness	225mic
Liner Weight	120g/m ²
Adhesive Weight	18g/m ²
Total Weight	238g/m ²
Initial Tack	>10
24hr 180° Peel	>8
Application Temperature	10-35°C
Service Temperature	-20 ~ +70°C

Product Code	Width (mm)	Length (m)
INV214405 - Gloss	1370	50
INV214408 - Matt	1370	50

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.