

## ASPHALT WALK®

AsphaltWalk® is designed to be used for short to midterm applications dependent on where the product is applied. The product can be used on asphalt, cement and untreated stone, pavement and many more surfaces. The material can easily be removed from such surfaces. AsphaltWalk® is designed to be very robust against abrasion and other influences caused by normal use of the product. The special adhesive is designed to work outdoor on rough surfaces.

### Durability

The durability of AsphaltWalk® is dependent the mechanical use of the surface where it is applied. We recommend a maximum use of 3–6 months. Life time can be significantly extended with EasyProtect liquid varnish.

### Printing method

UV curable inks screen printing and latex.

### Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

### Waste handling

AsphaltWalk® is designed to be fully recyclable. Used material and production waste can be handled as "aluminum waste".



### Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.



### Uses

- Shop entries, pedestrian areas & stairways
- Bus, tramway or metro stations, airports
- Sport events: Motor sport events, marathons
- Car, motorbike & general vehicle resellers
- Museums, meetings and other cultural events
- Petrol stations
- Car parks - indoor and outdoor including driveways
- Signalisations and road markings

### Features & Benefit

- Easy to apply and remove
- Suitable for rough surfaces
- Slip resistant
- PVC free

Distributed in the UK by:

**INNOTECH**

innotechdigital.com / 01530 512 731 / sales@innotechdigital.com



## Technical Information

## AsphaltWalk

Size	Width: 1.22 m      Length: 10.00 m, 15.00 m, 30.48 m	
Material	Coated soft aluminum (polyurethane)	220 $\mu$ +/- 10 $\mu$
Adhesive	Permanent acrylic solvent	80 $\mu$ +/- 5 $\mu$
	Total weight	428 g/m <sup>2</sup>
Certificates	Slip-resistance	R12 / 67212F
	Flame resistance / Flammability	M1 / F2 / SF3
	Surfaces roughness (SRT)	55
Application	Minimum application temperature	+10°C / +50°F

Peel Adhesion to	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	80oz/in (88N/100 mm)	50oz/in (55N/100mm)	70oz/in (77N/100mm)
24 hours dwell	100oz/in (110N/100 mm)	60oz/in (66N/100 mm)	80oz/in (88N/100 mm)

## Chemical Resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	I	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion  
 I = recommended for intermittent exposure only  
 NR = not recommended

\* Colour and lot variances of coated surfaces including paints, powder coatings, lacquers, stains and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface. \*\*At temperatures below +10 °C the surface has to be pre-treated with a gas burner.

Distributed in the UK by:

**INNOTECH**

innotechdigital.com / 01530 512 731 / sales@innotechdigital.com