

PANORAMA PROTECT

panoRama Protect is a highly transparent and slightly glossy laminate, which has been specially developed for laminating print media with increased transparency but can also be printed as a highly transparent film. The product is excellent for medium-term outdoor as well as indoor use. Additional UV protection is built into the over laminating film to help resist color fade caused by ultraviolet light. The perfect clarity (low haze) combined with high UV protection makes panoRama Protect the perfect match with panoRama one way vision window film. Don't forget: In order to protect your perforated window film from dust, humidity or contaminations while maintaining perfect transparency even in rain, lamination is essential!

Durability

Outdoor: Up to 2 years in mid European conditions
Indoor: Up to 3 years

Printing method

Solvent, eco-solvent, UV curable inks and screen printing.

Shelf life

1 year, stored at +15°C to +25°C (+59°F to +77°F) and relative humidity between 45% and 70%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.



Advice

Please check our applying and removal advices for panoRama.

Uses

All panoRama one-way-vision films applied on curved or flat surfaces
Especially developed to cover perforated film so that no dust, humidity or other contamination can penetrate the perforation
Recommended for applications where the best UV resistance and clarity is required even at extreme conditions
Wherever perfect visibility is required

Features & Benefit

For all types of printing method such as digital solvent, eco-solvent, screen printing or UV curable
Laminate stripes can be used as edge guard
Can also be used as a high transparency printing film
Excellent transparency



Distributed in the UK by:

Technical information
panoRama Protect

Size	Width: 1.372 m 1.524 m	Length: 25.00 m, 50.00 m 50.00 m	
Material	Vinyl film		75µ +/- 10µ
Adhesive	Clear permanent acrylic (solvent based) adhesive		
Laminate method	cold		
Liner	Frosted polyester film		50µ +/- 10µ
Application	Shrinkage		0 %
	Cohesion/ ultimate adhesion		High/ high
	Chemical resistance		No effects
	Tack		Medium
	Minimum application and removal temperature		+10°C / +50°F
	Minimum service range temperature		- 10°C / +14°F

Distributed in the UK by:

INNOTECH

innotechdigital.com / 01530 512 731 / sales@innotechdigital.com