

201-OAP SERIES

FLEXIBLE WHITE MATTE PVC - PERMANENT ADHESIVE

201-OAP Series is a 85 mic premium matte white flexible calendered vinyl film coated with 200-5031 permanent gray acrylic pressure sensitive adhesive laminated to a 135 gsm layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. Adhesive 200-5031 offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 135 gsm liner offers excellent product layflat in a variety of ambient conditions.

Applications	201-OAP Series is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.	
Thickness	Film	85 mic.
	Adhesive	25 mic
	Liner	135 gsm.
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature	+4,4°Celsius
	Service temperature	-40°C to +82°C.
Expected Exterior Exposure	Up to 5 years.	
Adhesion	To stainless steel	10,94 N/25mm
Average bond	PSTC-101 Method A with 24 hr. dwell at 21°C and 50% relative humidity. Typical values. Individual values may vary. Test your application thoroughly.	
Water Resistance	Good. Test if immersed.	
Humidity Resistance	Good.	
Solvent Resistance	Good.	
Storage Stability	6-month shelf life when stored at 21°C and 50% relative humidity	
Product Series	1,37m x 50m 1,52m x 50m	