

204 SERIESFLEXIBLE GLOSS WHITE PVC - REMOVABLE ADHESIVE

204 Series is a 75 mic premium white gloss flexible calendared vinyl film coated with 200-4982 removable acrylic pressure sensitive adhesive laminated to a 135 gsm layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems.

Applications 204 Series is designed for temporary interior or exterior signage, decals, nameplates,

diecut letters and point-of-purchase displays. Not designed for coated/ sealed/ treated

stainless steel, brass or bronze surfaces.

Thickness Film 75 mic.

Adhesive 25 mic Liner 135 gsm.

(Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature +4,4°Celsius

Service temperature -40°C to +82°C.

Expected Exterior Exposure Removable up to 1 year under normal conditions.

Adhesion To glass 1,37 to 4,10 N/25mm

To standard test panels 1,37 to 4,10 N/25mm

Tested according to PSTC-1 with 24-hour dwell at 21°C and 50% relative humidity.

Typical values. Individual values may vary. Test thoroughly before production.

Water Resistance Good. Test if immersed.

Humidity Resistance Good.

Solvent Resistance Good.

Storage Stability 6-month shelf life when stored at 21°C and 50% relative humidity

Product Series 1,37m x 50m

1,52m x 50m

RecommendationsCompletely evaporate ink solvents before application. Failure to do so may facilitate sol-

vent penetration resulting in premature vinyl degradation