

Kinetix Ferrous Sheet White Matt PP 0.26mm

A ferrous material with a PP base designed for indoor applications which is easy to apply, remove and change without leaving any residue, and features an anti rust coating.

Suitable for use with:



Order Code	W (mm)	L (mm)	Thickness (mic)
INM100250	1070	50	260
INM100253	1270	50	260
INM100256	1600	50	260

Kinetix Ferrous Sheet White Matt PP 0.26mm

TECHNICAL SPECIFICATIONS

Properties	Result
Lifting Weight	≥3.5g/cm ²
Total Thickness	248mic (±25)
Weight	320g/m ² (±32)
Whiteness	80, 90
Gloss 60°	3, 8
Opacity	100%
Water Resistance	Medium-High
Working Conditions	15°C - 30°C and 30-60% humidity
Application Conditions	Daily temperature and humidity change within 20°C and 30% respectively
Storage Conditions	Sealed and out of sunlight. Temperature range between 10°C and 35°C, and 20-70% humidity
Shelf Life	12 months in storage conditions. Use within one month from opening.

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.