

Kinetix Magnetic Sheet White Matt 0.3mm

Kinetix Magnetic Sheet is a specially formulated inkjet receptive vinyl surface for use on most wide-format, solvent based and eco-solvent based inkjet printers with a non ferrous transport path.

This product is ideal for retail applications where the advertising message is changed frequently, for example shop window displays. Domestic environments

The advanced lamination process, superior product compounding and exclusive barrier coating are all included at no additional cost!

FEATURES AND BENEFITS

- Lead free product
- Has unique flexibility characteristics. It can be folded and twisted without damaging any of the magnetic properties.
- Can be easily drilled, punched, scissor cut, knife cut and die cut.

Suitable for use with:



Order Code	W (mm)	L (mm)	Thickness (mm)
INM100106	1070	30	0.3
INM100112	1370	30	0.3
INM100115	1524	30	0.3

Kinetix Magnetic Sheet White Matt 0.3mm

TECHNICAL SPECIFICATIONS

Properties	Result	Unit
Thickness	0.3	Mm
Weight	700	g/m2
Whiteness	85-95	Wb
Brightness	2-5	Gs
Tensile Strength (Vertical)	40~50	MPa
Tensile Strength (Parallel)	30~40	MPa
Breaking Elongation Ratio (Vertical)	25~40	%
Breaking Elongation Ratio (Parallel)	40~55	%
Pull strength	7	g/cm2
Guass	110	Gs

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.