

## Laminated Frontlit PVC Banner 280

Lightweight and cost effective PVC Banner with a strong weave for promotional banner applications.

### FEATURES AND BENEFITS

- Suitable for indoor and outdoor use
- Available in 3m and 3.2m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm2)
ISB274930	3000	100	280
ISB274561	3200	100	280

# Laminated Frontlit PVC Banner 280

## TECHNICAL SPECIFICATIONS

Item	Test Method	Data
Weight	DIN53352 BS3424	280 g/sq.m
L W	DIN53354 BS3424	Warp - 1050 N/5cm Weft - 900 N/5cm
Tearing Strength L W	DIN53356 BS3424	Warp - 200 Ncm Weft - 150 Ncm
Temperature Re- sistance	DIN53372 BS3424	-20 - +70 degrees
Fire Rating		On request
Width		1370/1600/3200

*NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of  $\pm 5\%$ . Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.*