

Laminated Frontlit PVC Banner 440

Our bestselling product for all general promotional banner applications

FEATURES AND BENEFITS

- Suitable for indoor and outdoor use
- Available up to 3.2m and 5.0m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm2)
ISB274195	760	30	440
ISB274522	760	50	440
ISB274192	1100	30	440
ISB273925	1100	50	440
ISB273934	1370	30	440
ISB274165/ISB274849	1370	50/100	440
ISB274864	1524	30	440
ISB274189	1600	30	440
ISB274168/ISB274771	1600	50/100	440
ISB273967	1900	50	440
ISB273973/ISB274774	2050	50/100	440
ISB274171/ISB274762	2200	50/100	440
ISB274174	2500	50	440
ISB274525	2600	50	440
ISB274465/ISB274582	3200	65/100	440
ISB274936	4000	65	440
ISB274933	5000	65	440

Laminated Frontlit PVC Banner 440

TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight	DIN53352 BS3424	440	g/sq.m
Tensile Strength (W/F)	DIN 53354 BS3424	798/495	N/5cm
Tear Resistance (W/F)	DIN 53356 BS3424	125/107	N/5cm
Welding Adhesion	DIN 53357 BS3425	60	N/5cm
Temperature Resistance	DIN 53372 BS3424	-20 - +70	°C
Max Width	DIN EN ISO 2286-1	5.0	Meter
Flame Retardant	NFPA-701, DIN4102-B1	On request	

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.