

Max-Flat Light-Stop Roll-Up Media 330

The 330gsm light weight grey back banner is a PET laminated with white printable PVC substrate.

The material is with grey back for high opacity, matte finish for vivid graphic printing. It is no curling and extremely clear edge for application.

Ideal for roll up banners as well as other application.

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm2)
ISB275448	914	30	330

Max-Flat Light-Stop Roll-Up Media 330

TECHNICAL SPECIFICATIONS

PARAMETER		VALUE
Physical Property	Tensile Strength (N/5cm)	902x873
	Tear Strength (N)	25x23
	Peeling Strength (N/5cm)	50
Weight / GSM		330
Finish		Matte
Available size		914mm
Fire Retardant Level		-
Shelf time		12 Months
Application temperature		5-130 °C
Durability		12 Months

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.