

PET One Way Vision Without Adhesive

A one way vision without adhesive is ideal for use on x banners, window displays or hanging banners.

The VistaMAX PET One Way Vision is not only PVC-Free and 100% recyclable, it is also very tough and can be used for long term applications.

Suitable for use with:



Order Code	W (mm)	L (mm)	Thickness (ums)
INV214111	1370	50	200

PET One Way Vision Without Adhesive

Technical Data

Property	Test Method	Result
Film Weight	ISO 4591:1992	200micron white/black PET film
Release Paper		50 micron white PET
Dimensional Stability	FINAT TM14	No shrinkage in cross direction, in length
Temperature Resistance		Adhered to aluminium -20°C to +100°C, no variation
Diameter of hole		1.5mm
Perforated ratio		30%
Shelf life		Up to 3 years
Storage		One year out of direct sunlight at 23°C and 50% humidity
Application Temperature		Min +10°C
Weather Resistance		3 years

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.