

Premium Frontlit PVC Banner 450 FR B1

High quality PVC Banner with high tear resistance and durability for indoor and outdoor applications

FEATURES AND BENEFITS

- Fire rated to B1 certification
- Suitable for indoor and outdoor use
- Premium grade product
- Available up to 3.2m and 5.0m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm2)
ISB274786	950	30	450
ISB274597	1100	30	450
ISB274600	1370	30	450
ISB2745765	1524	30	450
ISB274603	1600	30	450
ISB274942	1600	50	450
ISB274606	2050	50	450
ISB275642	2500	60	450
ISB274903	3200	65	450
ISB275316	5000	65	450

Premium Frontlit PVC Banner 450 FR B1

TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight	DIN53352 BS3424	450	g/sq.m
Tensile Strength (W/F)	DIN 53354 BS3424	2090.1/1867.4	N/5cm
Tear Resistance (W/F)	DIN 53356 BS3424	309.8/293.2	N/5cm
Opacity (%)/Transmittence		99	%
Welding Adhesion	DIN 53357 BS3425	80	N/5cm
Temperature Resistance	DIN 53372 BS3424	-20 - +70	°C
Max Width	DIN EN ISO 2286-1	5.0	Meter
Flame Retardant	NFPA-701, DIN4102-B1	B1	
Peeling Strength		42	N/5cm

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.