

## Premium PVC Backlit Banner Matt 510 FR B1

Translucent Matt PVC Banner developed for backlit signage applications and stretch frames.

### FEATURES AND BENEFITS

- Fire rated for B1 certification
- Suitable for indoor and outdoor use
- Available in 3.2m and 5.0m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm <del>l</del> )
ISB274585	3200	60	510
ISB274678	5000	60	510

# Premium PVC Backlit Banner Matt 510 FR B1

## TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total weight	DIN53352 BS3424 method5A	510	g/sq.m
Tensile strength (W/F)	DIN53354 BS3424 method6A	2100/1850	N/5cm
Tear Resistance (W/F)	DIN53356 BS3424 method 7A	300/250	N/5cm
Welding Adhesion	DIN53357 BS3425 method9B	80	N/5cm
Temperature Resistance	DIN 53372 BS3424 method10	-20 - +70	°C
Max width		5.0	Meter
Flame Retardant		B1	

*NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.*