

Premium PVC Blockout Double-Sided Banner 750 FR B1

Extra strong double sided banner, suitable for demanding outdoor applications

FEATURES AND BENEFITS

- Fire rated to B1 certification
- Suitable for indoor and outdoor use
- Premium grade product
- Available in 3.2m and 5.0m widths
- Double sided printing

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm 2)
ISB274564	1100	50	750
ISB274567	1370	50	750
ISB274570	1600	50	750
ISB274726	2500	50	750
ISB274573	3200	50	750
ISB274576	5000	50	750

Premium PVC Blockout Double-Sided Banner 750 FR B1

TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight	DIN53352 BS3424	750	g/sq.m
Tensile Strength (W/F)	DIN 53354 BS3424	2300/2100	N/5cm
Tear Resistance (W/F)	DIN 53356 BS3424	350/300	N/5cm
Welding Adhesion	DIN 53357 BS3425	80	N/5cm
Temperature Resistance	DIN 53372 BS3424	-20 - +70	°C
Max Width		5.0	Meter
Flame Retardant	NFPA-701, DIN4102-B1	B1	

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.