

## PVC Mesh Without Liner 290

290g/m<sup>2</sup> PVC Mesh Banner without backing Liner, suitable for the largest banner applications

### FEATURES AND BENEFITS

- Suitable for indoor and outdoor use
- Available in 3.2m and 5.0m widths

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm <sup>2</sup> )
ISB274621	2500	50	290
ISB274915	3200	65	290
ISB274960	5000	65	290

# PVC Mesh Without Liner 290

## TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight	DIN53352 BS3424	270	g/sq.m
Tensile Strength (W/F)	DIN 53354 BS3424	1200/1100	N/5cm
Tear Resistance (W/F)	DIN 53356 BS3424	300/280	N/5cm
Temperature Resistance	DIN 53372 BS3424	-20 - +70	°C
Max Width	DIN EN ISO 2286-1	5.0	Meter
Air Loading	ISO 9237	2458	mm/s
Flame Retardant	N/A		
Environmental	EN-71 RoHs	On Application	

*NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of  $\pm 5\%$ . Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.*