

## Seemee



## M

## **Seemee Frontlit**

	Ultra matt	Matt	Standard easy	Night+Day
	Technical properties			
Product reference	B7615	B7613	B7945	B7939
Application	banner, billboard, display	banner, billboard, display	banner, billboard, display	banner, billboard, display
Printing technology	solvent, UV, latex	solvent, UV, latex	solvent, UV, latex	solvent, UV, latex
Support cloth DIN ISO 2076	PES	PES	PES	PES
Type of coating	PVC, phthalate-free	PVC, phthalate-free	PVC	PVC
Weight DIN EN ISO 2286-2	450 g/m² 13,3 oz/sq.yd	480 g/m <sup>2</sup> 14,2 oz/sq.yd	450 g/m² 13,3 oz/sq.yd	500 g/m <sup>2</sup> 14,7 oz/sq.yd
Width DIN EN ISO 2286-1	250 cm - 500 cm 98 in 197 in.	160 cm - 320 cm 63 in 126 in.	320 cm - 500 cm 126 in 197 in.	320 cm - 500 cm 126 in 197 in.
	Roll length			
For all widths	50 lm • 54.68 yd	50 lm • 54.68 yd	50 lm • 54.68 yd	50 lm • 54.68 yd
	Physical properties			
Tensile strength (warp/weft) DIN EN ISO 1421	250/200 daN/5 cm 562/450 lbs/2 in	250/200 daN/5 cm 562/450 lbs/2 in	250/200 daN/5 cm 562/450 lbs/2 in	250/200 daN/5 cm 562/450 lbs/2 in
Tear strength (warp/weft) DIN EN 53363	40/30 daN 90/67 lbs	40/30 daN 90/67 lbs	25/20 daN 56/45 lbs	25/20 daN 56/45 lbs
	Fire resistance			
Rating	-	-	BS 476 Part 6 & 7 Class 0 ADTM E 84 Method 1/NFPA 701 Schwerbrennbar-Q1-Tr1/ONORM A 3800-1	<b>ASTM E</b> 84 BS 5867 Part 2
Euroclass EN 13501-1	B-s2,d0	B-s2,d0	B-s1,d0	B-s2,d0
	Management system			
	Quality: ISO 9001 • En	vironment: ISO 14001	• Energy: ISO 50001	







<sup>&</sup>lt;sup>1</sup> Summarizes the group's CSR project focused on human, to align economic performance and positive impact.

The technical data above are averaged values with a +/-5% tolerance.

The purchaser of our products is responsible for their application or transformation in relation to possible third party rights. The purchaser of our products is responsible for their installation in compliance with the standards, working practices and safety regulations of their destination country. Please refer to our warranty document with regard to contractual liability.

Values quoted in this document are commonly used test results for design purposes. They are given for information only in order to offer our customers optimum usage of our products. Our products are subject to improvements resulting from technical developments and we reserve the right to modify their characteristics at any time. The purchaser of our products is responsible for checking the above data.

The colours and textures presented are included for information only.

