

Monomeric Permanent Clear Matt Vinyl 80

80mic clear matt vinyl with a permanent acrylic adhesive, and a 145mic one side siliconised clay coated Kraft liner. Designed to be applied on a number of surfaces including ABS, PS, PVC and is used in advertising and promotional applications such as window graphics, outdoor and indoor posters, billboards and signs, as well as flat vehicle surfaces.

Suitable for use with:



Order Code	W (mm)	L (mm)	Thickness (ums)
INV212216	1370	50	80
INV212222	1600	50	80

Monomeric Permanent Clear Matt Vinyl 80

Technical Data

Property	Test Method	Result
Face Film		
Colour & Finish		Clear Matt
Weight	ISO-536	110gsm \pm 10%
Thickness	ISO-534-80	80 ums \pm 10%
Adhesive		
Type		Acrylic Permanent
Minimum Application Temperature		+10°C
Service Temperature		-30°C/+120°C
Shear		Medium
Tack		Medium N/25mm
Final Adhesion		High N/25mm
Liner		
Type		One side siliconised clay coated Kraft
Colour & Finish		White
Weight	PP-032-ISO 536	135gsm \pm 10%
Thickness	ISO 534	145ums \pm 10%
Transparency	DIN 53 147-64	N/A

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of \pm 5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.