

TECHNICAL SPECIFICATIONS

VISTAFLEX® KCBA450 PREMIUM KNIFE COATED PVC BACKLIT BANNER 450G/M2

Features & Benefits

- Extra strong and durable backlit banner
- Designed to diffuse light from behind
- Available up to 3.2m and 5m widths
- Applications: Out-of-home advertising and flex face signs

Printing

- The material should reach room temperature and a relative humidity of approx. 50% prior to printing.
- Ensure the material is kept free of dust, dirt and static. We recommend using gloves when handling the material.
- Conduct a print test prior to printing the material for a live project.
- Rolls are wound Print Side In (PSI)
- Suitable for printing with Solvent, Eco-Solvent, Latex and UV-C printers.

Storage

- We recommend storing the material in its original tube and wrapping when not in use.
- Material can be stored for up to 2 years when stored in the original packaging
- Store between 20°C and 25°C at 50% relative humidity

Laminating

- This material does not require lamination. However, should the user decide to apply liquid laminate, it is their responsibility to test.



Characteristic	Result
Base Fabric	100% Polyester
Coating	PVC
Weight	450g/m2
Tensile Strength	
Warp	3000 N/50mm
Weft	3000 N/50mm
Fire Certification	B1

Product Code	Width (mm)	Length (m)
ISB276359	3200	50
ISB276362	5000	50

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.