

Signage

Pro, II, IV Heavy, IV Light



Seemee Signage

	Pro	II	IV Heavy	IV Light
--	-----	----	----------	----------

Technical properties

Product reference	B3832	B1150	B1149	B3852
Application	long-term signage*	long-term signage*	long-term signage*	long-term signage*
Printing technology	UV, Latex, solvent	UV, Latex, solvent	UV, Latex, solvent	UV, Latex, solvent
Support cloth DIN ISO 2076	PES	PES	PES	PES
Type of coating	PVC	PVC	PVC	PVC
Weight DIN EN ISO 2286-2	530 g/m ² - 15,6 oz/sq. yd	550 g/m ² - 16,2 oz/sq. yd	650 g/m ² - 19,2 oz/sq. yd	550 g/m ² - 16,2 oz/sq. yd
Width DIN EN ISO 2286-1	320 cm - 126 in.	320 cm - 126 in.	320 cm - 126 in.	500 cm - 197 in.
Light transmission	~ 33 % (@550nm)	~ 17,52 % (@550nm)	~ 16,05 % (@550nm)	~ 18,95 % (@550nm)

Roll length

For all widths	50 lm • 54.68 yd	50 lm • 54.68 yd	50 lm • 54.68 yd	50 lm • 54.68 yd
----------------	------------------	------------------	------------------	------------------

Physical properties

Tensile strength (warp/weft) DIN EN ISO 1	230/200 daN/5cm 517/450 lbs/2 in	300/300 daN/5cm 674/674 lbs/2 in	300/300 daN/5cm 674/674 lbs/2 in	300/300 daN/5cm 674/674 lbs/2 in
Tear strength (warp/weft) DIN EN 53363	30/28 daN 67/63 lbs	30/30 daN 67/67 lbs	30/30 daN 67/67 lbs	30/30 daN 67/67 lbs

Fire resistance

Rating	Method 1/NFPA 701 B1/DIN 4102-1	-	Method 2/NFPA 701 B1/DIN 4102-1	Method 2/NFPA 701
Euroclass EN 13501-1	-	B-s3,d0	-	B-s3,d0

Management system

Quality: ISO 9001 • **Environment:** ISO 14001 • **Energy:** ISO 50001

Certifications, labels, warranty



¹ Summarizes the group's CSR project focused on human, to align economic performance and positive impact.

* please contact us

The technical data above are averaged values with a +/-5% tolerance.

The purchaser of our products is responsible for their application or transformation in relation to possible third party rights. The purchaser of our products is responsible for their installation in compliance with the standards, working practices and safety regulations of their destination country. Please refer to our warranty document with regard to contractual liability.

Values quoted in this document are commonly used test results for design purposes. They are given for information only in order to offer our customers optimum usage of our products. Our products are subject to improvements resulting from technical developments and we reserve the right to modify their characteristics at any time. The purchaser of our products is responsible for checking the above data.

The colours and textures presented are included for information only.