

# TECHNICAL DATA SHEET

## GF 202

### 3.4 MIL MATTE WHITE VINYL CLEAR LOW-TACK REMOVABLE ADHESIVE

GF 202 is a 3.4 mil polymeric matte white calendered vinyl coated with a clear low-tack removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This vinyl is designed to accept a variety of solvent-based, eco-solvent, latex and UV curable inks common to wide format digital printing systems. GF 202 is a removable vinyl designed for interior or exterior signage, decals, nameplates, and point-of-purchase displays. The 90# liner offers excellent product layflat in a variety of ambient conditions along with ease of application of large format graphics.

PRODUCT NAME	202
<b>FILM</b>	
Film Type	White Polymeric Vinyl
Film Thickness (mils/ $\mu$ m)	3.4 / 86 (+/- 10%)
Film Weight (gsm)	120
Gloss (60°)	$\leq$ 20
Opacity (%)	93
Tensile Strength (lbs/in)	MD $\geq$ 3000 / CD $\geq$ 2600
Elongation (%)	MD $\geq$ 90 / CD $\geq$ 150
Dimensional Stability (FTM 14)	MD $\leq$ 0.50 mm / CD $\leq$ 0.50 mm
<b>ADHESIVE</b>	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils/ $\mu$ m)	0.8-1.0 / 20-25
Adhesive Color	Clear
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	0.09-0.30 / 0.4-1.3
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	0.09-0.50 / 0.4-2.2
Peel Strength on Glass (lbs/in) / (N/25mm) 15 min	0.2-0.5 / 0.9-2.2
Peel Strength on Glass (lbs/in) / (N/25mm) 24 hrs	0.2-0.5 / 0.9-2.2
<b>LINER</b>	
Liner Weight (#/gsm)	90 / 145
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils/ $\mu$ m)	6.7 / 170
Release Force @ 300" / min (g/2")	80-130
<b>PERFORMANCE GUIDANCE</b>	
Application Temperature	$\geq$ +40 °F
Service Temperature	-40 °F to 180 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	5 years
Removability	1 year

# TECHNICAL DATA SHEET

## GF 202- 3.4 MIL MATTE WHITE VINYL CLEAR LOW-TACK REMOVABLE ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
<p><b>APPLICATION</b></p> <ul style="list-style-type: none"> <li><input type="radio"/> WET APPLY</li> <li><input checked="" type="radio"/> DRY APPLY</li> <li><input type="radio"/> LAMINATING</li> <li><input type="radio"/> MOUNTING</li> <li><input checked="" type="radio"/> DIE CUTTABLE</li> <li><input type="radio"/> HOT STAMP</li> <li><input type="radio"/> THERMAL DIE</li> <li><input checked="" type="radio"/> FLATBED CUTTABLE</li> </ul>	<ul style="list-style-type: none"> <li><input checked="" type="radio"/> POP/RETAIL</li> <li><input type="radio"/> WALL</li> <li><input type="radio"/> WRAP</li> <li><input checked="" type="radio"/> WINDOW</li> <li><input type="radio"/> FLOOR</li> <li><input type="radio"/> TRANSLUCENT</li> <li><input type="radio"/> FLEET</li> <li><input checked="" type="radio"/> GENERAL SIGNAGE</li> <li><input checked="" type="radio"/> OUTDOOR (SHORT TERM)</li> <li><input checked="" type="radio"/> OUTDOOR (LONG TERM)</li> </ul>	<ul style="list-style-type: none"> <li><input checked="" type="radio"/> SOLVENT</li> <li><input checked="" type="radio"/> ECO-SOLVENT</li> <li><input checked="" type="radio"/> LATEX</li> <li><input checked="" type="radio"/> UV CURABLE</li> <li><input checked="" type="radio"/> SCREEN</li> <li><input checked="" type="radio"/> OFFSET (UV CURABLE)</li> <li><input type="radio"/> OFFSET (CONVENTIONAL)</li> </ul>
<p><b>SUBSTRATES</b></p> <ul style="list-style-type: none"> <li><input type="radio"/> OEM PAINTED METAL</li> <li><input type="radio"/> PAINTED ALUMINUM</li> <li><input type="radio"/> STAINLESS STEEL</li> <li><input type="radio"/> LOW-ENERGY SURFACES</li> <li><input checked="" type="radio"/> ACRYLIC</li> <li><input checked="" type="radio"/> GLASS</li> <li><input type="radio"/> POLYESTER</li> </ul>		

### FAQS

What applications is GF 202 intended for?	GF 202 is designed for temporary interior or exterior signage, decals, nameplates, point-of-purchase displays and general signage. Not designed for coated/sealed/treated stainless steel, brass or bronze surfaces found on elevator doors.
How long can GF 202 be applied to windows?	GF 202 is rated for 1 year clean removability. If the vinyl is left on for longer, it will not adversely affect the glass surface, but may be harder to remove, including the possibility of adhesive transfer.