

Vertex Texture Polyester Coated Fabric 240 FR Bs1 d0

Versatile 100% polyester textured textile at 240gsm for a wide range of applications including retail, hanging displays, exhibitions, canvas frames and wall paper.

FEATURES AND BENEFITS

- PVC Free material and 100% recyclable
- Fire rated to Bs1 d0 certification.
- Available in widths up to 3.2m
- Premium grade product
- Material is also available in white or blue back
- 100% polyester coated fabric

Suitable for use with:



ECO IMPACT
RATING



Order Code	W (mm)	L (mm)	Weight (gsm)	
ISB275983	1250	50	240	Grey Back
ISB275986	1370	30	240	Grey Back
ISB275989	1370	50	240	Grey Back
ISB275992	1600	50	240	Grey Back
ISB275995	1800	50	240	Grey Back
ISB275998	2500	50	240	Grey Back
ISB276001	3200	50	240	Grey Back
ISB275980	914	50	240	Grey Back

Vertex Texture Polyester Coated Fabric 240 FR Bs1 d0

TECHNICAL SPECIFICATIONS

Properties	Result	Unit
Weight	240	g/m ²
Tensile Strength - Warp Tensile Strength - Weft	981 820	N/5cm
Tearing Strength - Warp Tearing Strength - Weft	239 231	N/5cm
Peeling Strength	Unpeelable	

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.