

Tarpaulin

Supreme, Extra



Seemee Tarpaulin

	Supreme	Extra
Technical properties		
Product reference	B2011	B2033
Application	printable truck cover	printable truck cover
Printing technology	solvent, UV, latex	solvent, UV, latex
Support cloth DIN ISO 2076	PES	PES
Type of coating	PVC	PVC
Weight DIN EN ISO 2286-2	670 g/m ² - 19,8 oz/sq.yd	900 g/m ² - 26,5 oz/sq.yd
Width DIN EN ISO 2286-1	320 cm - 126 in.	300 cm - 118 in.
Roll length		
For all widths	50 lm • 54.68 yd	50 lm • 54.68 yd
Physical properties		
Tensile strength (warp/weft) DIN EN ISO 1421	300/300 daN/5 cm 674/674 lbs/2 in	400/380 daN/5 cm 899/854 lbs/2 in
Tear strength (warp/weft) DIN 53363	30/30 daN 67/67 lbs	45/40 daN 101/90 lbs
Fire resistance		
Rating	-	ISO 3795 < 100 mm/min
Management system		
Quality: ISO 9001 • Environment: ISO 14001 • Energy: ISO 50001		
Certifications, labels, warranty		



¹ Summarizes the group's CSR project focused on human, to align economic performance and positive impact.

The technical data above are averaged values with a +/-5% tolerance.

The purchaser of our products is responsible for their application or transformation in relation to possible third party rights. The purchaser of our products is responsible for their installation in compliance with the standards, working practices and safety regulations of their destination country. Please refer to our warranty document with regard to contractual liability.

Values quoted in this document are commonly used test results for design purposes. They are given for information only in order to offer our customers optimum usage of our products. Our products are subject to improvements resulting from technical developments and we reserve the right to modify their characteristics at any time. The purchaser of our products is responsible for checking the above data.

The colours and textures presented are included for information only.