

Vertex Glacier Display 180gsm FR B1

Ideal for large-scale soft signage applications, our 180gsm Vertex Glacier Display textile is most often used for backlit tension fabric displays in retail spaces, airports, car showrooms or museums. The coated, 100% polyester fabric is crease resistant for fuss free, high impact results.

FEATURES AND BENEFITS

- Totally crease free material
- PVC Free
- Consistent diffusion for excellent backlit
- Allows for a variety of textile applications
- REACH compliant, environmentally friendly material.

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gsm)
IST275344	1600	50	180
IST275380	2600	100	180
IST275263	3200	50	180
IST275347	3200	100	180
IST275362	5050	50	180

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.

Vertex Glacier Display 180gsm FR B1

TECHNICAL SPECIFICATIONS

Properties	Test method	Result	Unit
Whiteness		>115	%
Total Weight	DIN EN ISO 2286-2	180	g/sq.m
Thickness		230	Ums
Max Width		5.05	Meter
Opacity		>80	%
Flame Retardant	DIN4102-B1	B1	-
Environmental	REACH	Yes	-

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.