

VistaMAX E1140LT

PVC Free Repositionable Film White 115mic

- Made with 115mic white PET film and a 75mic PET liner for stability and durability.
- Silicone Adhesive: Low-tack, residue-free, removable, and repositionable for easy and clean installation.
- Suitable for eco-solvent, latex, and UV printing.
- Ideal for labelling, flat posters, window advertising, and seasonal decorations.
- Adheres to smooth surfaces such as glass, metal, and plastic.

Suitable for use with:



Order Code	W (mm)	L (m)
INV214489	1370	50

Instructions

Printing Instructions

- Maintain a temperature of $25 \pm 5^{\circ}\text{C}$ and a relative humidity of $50\% \pm 10\%$.
- Use a clean, dust-free environment for optimal results.
- Adjust the printer settings to achieve the best printing conditions before starting.

Application Instructions

- Suitable for indoor use only.
- Ensure the product surface is completely flat before application.
- Apply to a clean, smooth, and dust-free substrate surface.
- It is recommended to use a light spray of water to assist with installation.

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.

VistaMAX E1140LT

PVC Free Repositionable Film White 115mic

TECHNICAL SPECIFICATIONS

Properties	Result	Unit
Film Thickness	115 ±7	Mic
Total Thickness	155 ±9	Mic
Film Weight	150 ±9	g/m ²
Total Weight	205 ±12	g/m ²
180° Peel Strength	2-10	g/25mm
24hr 180° Peel	2-10	g/25mm
Breaking Elongation	>80	%
Dimensional Stability CD	<0.1	In
Service Temperature Range	-30~+130	°C

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.