

Technical Datasheet

E204OPECO

GLOSS VINYL / GREY REMOVABLE ADHESIVE

E204OPECO is an 90µ gloss white economic polymeric PVC Film, coated with a removable grey pressure sensitive Solvent adhesive on a DSPE Liner. Liner protects against Water and Moisture and no tunneling. E204OPECO accepts a variety of solvent-based, eco-solvent, latex and *UV curable inks common to wide format digital printing systems.

Applications: Short to medium term indoor or outdoor advertising and promotion. Can be used on flat or curved surfaces.

Thickness: 90µ ± 10%
Adhesive: Removable Grey Solvent Adhesive
Liner: 135 g/m² DSPE Liner

Application Temperature: Minimum application temperature > 10°C
Service temperature: -20°C to +70 °C

Adhesion: 6N/25mm - FINAT TM 1, after 24 hours, adhered to stainless steel
Dimensional stability MD: ≤ 0,9mm- FINAT 14
Dimensional stability CD: ≤ 0,5mm- FINAT 14
Tensile Strength: > 24N/mm² - DIN EN ISO 527-1
Elongation at break: > 160% - DIN EN ISO 527-1

Durability: Up to 5 years unprinted **

Recommendations: Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation. * For UV Curable inks, please consult with the ink manufacturer for specifics on ink flexibility.

Fire rating: Self-extinguishing, adhered to stainless steel.
Shelf life: at 23°C / 50% moisture 2 years *

* Average Value

** Under vertical outdoor exposure, based on Central Europe Climate

Product Codes:	E204OPECO-42	106,7 cm X 50 m
	E204OPECO-54	137,2 cm X 50 m
	E204OPECO-60	152,4 cm X 50 m