

Vistamax Quickdot Self Adhesive Vinyl 100mic

Vistamax Quickdot is a monomeric printable vinyl with a unique “dot” adhesive technology. The unique adhesive makes installation very easy, and also allows for effortless removability. It is perfect for indoor signage, window graphics, point of sale and display applications, especially in retail environments. For short term use, durability up to 3 years

It is available in matt white and clear gloss version.

Please see following page for technical specification.

Suitable for use with:



Order Code	W (mm)	L (mm)	Thickness (ums)
INV214285 White Matt	1370	50	100
INV214279 Clear Gloss	1370	50	100

Vistamax Quickdot Self Adhesive Vinyl 100mic

Technical Data

Property	Result	Test Method
Face thickness, without adhesive	100mic	ISO 534-80
Face thickness, with adhesive	120ic	ISO 534-80
Tensile strength (machine direction)	>25 N/cm	ISO 527
Elongation at break (machine direction)	>150%	ISO 527
Fire resistance on aluminium	Self-extinguishing	ISO 3795:1989
Dimensional stability (1 week @70 °C on glass)	0.5mm	FTM 14
Initial adhesion on glass (20 minutes)	1 N/25mm	FTM 1
Adhesion on glass (24 hours)	2 N/25mm	FTM 1
Final adhesion on glass (1 week)	3 N/25mm	FTM 1
Minimum application temperature	+10°C	
Service temperature	From -40 °C to +90 °C	
PE coated kraft paper liner	140 g/m2	ISO 536

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.