

BA190DS - Iceflow BacklitStretch Textile 190gm2

FEATURES AND BENEFITS

- 100% woven polyester fabric with white surface
- Slight stretch feature makes it perfect as a SEG Light Box and frame and Pop-up materials

Suitable for use with:



Order Code	W (mm)	L (m)	Weight (gsm)
IST375438	3200	25	190
IST375435	3200	100	190

TECHNICAL SPECIFICATIONS

Properties	Test method	Result
Total Weight	DIN EN ISO 2286-2, ASTM D 751	190 g/m2
Base Fabric	DIN 60001, ASTM D7641	100% Polyester
Weave Method	N/A	Woven
Shrinkage	195°C, 42sec	Warp ≤2%, Weft ≤3%
Light Transmittance	ANSI PH2.19, ISO 5/2	(48 +- 6)%
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test 1	
Recommend Fixation Temperature	N/A	190°C-210°C, 1-2min
Transfer Temperature	N/A	190°C-210°C, 1-2min
Yellowing temperature	30s	≥210°C

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.