

PAVUS, a.s. AUTHORIZED BODY 216 NOTIFIED BODY 1391 ACCREDITED CERTIFICATION BODY FOR PRODUCTS N° 3041

Address:

Prosecká 412/74, 190 00 Praha 9 – Prosek Tel.: 286 019 587 Fax: 286 019 590 Mail to: mail@pavus.cz, http://www.pavus.cz Branch: FIRE TESTING LABORATORY VESELÍ NAD LUŽNICÍ Čtvrť J. Hybeše 879 CZ 391 81 Veselí nad Lužnicí Czech Republic

> Phone:+420 381 477 418 Fax: +420 381 477 419 Mail to: veseli@pavus.cz

REACTION TO FIRE CLASSIFICATION REPORT





1 INTRODUCTION

- 1.1 This classification report defines the classification assigned to *Poplin Plus Art. No. 599200 129* in accordance with the procedures given in EN 13501-1:2007+A1:2009.
- 1.2 This classification report has 4 pages and it can be used or reproduced as a whole only.

2 DETAILED INFORMATION ON THE PRODUCT TO BE CLASSIFIED

2.1 General

The product *Poplin Plus Art. No. 599200 129* is made by the company PONGS Technical Textiles GmbH, Bahnhofstraße 21, DE 07919 Mühltroff, Deutschland. It is used free-hanging as substrate for digital print, promotional materials etc.

2.2 Product description

Thickness:	0.39 mm
Mass per unit area:	0.175 kg/m ²
Colour:	white
Composition:	100% PES textile

3 REPORTS AND RESULTS IN SUPPORT OF THIS CLASSIFICATION

3.1 Reports

Name of the Laboratory Address Accreditation number:	Name of sponsor of the Test Report	Report number Date of issue	Test method
PAVUS, a. s. Veselí nad Lužnicí ATL No 1026 Banhofstrasse 21 DE 07919 Mühltroff Deutschland	Pr-18-1.191 2018-10-05	EN 13823:2010+A1:2014	
	DE 07919 Mühltroff	Pr-18-1.192 2018-10-05	EN ISO 11925–2:2010



3.2 Results

Test method	Parameter		Results	
		Number of tests	Continuous parameter- mean	Compliance with parameters
EN 13823+A1	FIGRA _{0.2 MJ} (W/s)		0.0	≤ 120 (B)
	THR _{600s} (MJ)		0.0	≤7.5 (B)
	LFS < edge of specimen		-	yes (B)
	SMOGRA (m²/s²)	3	0.0	≤30 (s1)
	TSP600s (m²)		28.9	≤ 50 (s1)
	non-occurring of flaming droplets/particles		-	yes (d0)
EN ISO 11925 - 2	Fs ≤ 150 mm up to 60 s	6	-	yes (B)
Surface exposure	Filter paper non-ignition		-	yes (d0)
EN ISO 11925 - 2	Fs ≤ 150 mm up to 60 s	6	-	yes (B)
Edge exposure	Filter paper non-ignition		-	yes (d0)

4 CLASSIFICATION AND FIELD OF APPLICATION

4.1 Classification references

This classification was carried out in conformity with EN 13501-1:2007+A1:2009.

4.2 Classification

The product Poplin Plus Art. No. 599200 129 in relation to its reaction to fire behaviour is classified:

Reaction to fire class: B – s1, d0

4.3 The field of application

This classification is valid for the following product parameters:

Thickness:	0.39 mm
Mass per unit area:	0.175 kg/m²
Colour:	white
Composition:	cannot be changed



This classification applies for the following end-use applications:

Substrate:	free situated product without a substrate or with substrates of reaction to fire classes A1
Way of fixing: Joints:	mechanically with fittings of reaction to fire classes A1 without joints

5 RESTRICTIONS

This classification report does substitute neither the type approval nor the product certificate.

This classification is valid, unless the conditions, under which it was issued, have been changed. The sponsor may request the issuing authority to review the influence of changes to the classification validity.

Elaborated by:

Lenka Sobotová Fire testing laboratory

PAVUS, a. s. Autorizovaná osoba AO 216 Pobočka 391 81 Veselí nad Lužnicí ⊕ Approved by:

. Jaroslav Dufek TIFIK AVUS, a