

# Vertex Texture Linen PVC-Free Coated Polyester Grey Back FR B1 290g/m2

Versatile 100% polyester textured textile at 290gsm for a wide range of applications including retail, hanging displays, exhibitions, canvas frames and wall paper.

#### FEATURES AND BENEFITS

- PVC Free material and 100% recyclable
- Fire rated to B1 certification.
- Available in widths up to 3.2m
- Premium grade product
- 100% polyester coated fabric

#### Suitable for use with:









Order Code	W (mm)	L (mm)	Weight (gsm)	
ISB276242	3200	50	290	Grey Back



# Vertex Texture Linen PVC-Free Coated Polyester Grey Back FR B1 290g/m2

### TECHNICAL SPECIFICATIONS

Properties	Result
Weight (g/m)	290
Thickness (mic)	360
Tensile Strength (Warp) N/50mm Tensile Strength (Weft) N/50mm	1150 1100
Tearing Strength (Warp) N/50mm Tearing Strength (Weft) N/50mm	230 220
Peeling Strength (N/50mm)	Unpeelable

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of ±5%. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.