TECHNICAL SPECIFICATIONS

VISTAMAX® GE5080AE GLASS ETCH POLYMERIC FILM, CLEAR PERMANENT ADHE-SIVE, AIR RELEASE LINER 80MIC

Features & Benefits

- 5 year durability
- Frosted/sandblasted glass look
- Easy, bubble-free application
- No residue on removal

Printing

- The material should reach room temperature and a relative humidity of approx. 50% prior to printing.
- Ensure the material is kept free of dust, dirt and static.
 We recommend using gloves when handling the material.
- Conduct a print test prior to printing the material for a live project.
- Rolls are wound Print Side Out (PSO).
- Suitable for printing with Eco-Solvent and Solvent printers.

Application

• Suitable for application to flat or slightly curved surfaces

- This product is not designed for application to low energy surfaces
- It is the responsibility of the user to determine the suitability of the material for the application.
- Test the application with a small piece of the material prior to doing the full application

Storage


- We recommend storing the material in its original box and wrapping when not in use.
- Material can be stored for up to 12 months when stored in the original packaging
- Store between 20°C and 25°C at 50% relative humidity



Characteristic	Result	
Film Type	Polymeric calendared PVC	
Liner Type	Two sided PE coated, silicone paper 144gsm	
Adhesive Type	Clear micro-structure solvent acrylic permanent	
Film Thickness	80mic	
Adhesion	7 N/50mm	
Application Temperature	+10 - +40 °C	
Service Temperature	- 40 - +80 °C	

Product Code	Width (mm)	Length (m)
INV214504	1370	50

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.





.....