

## **Static Cling Clear Gloss 150mic**

Monomeric, electrostatic PVC Film (transparent gloss, 150mic) laminated on an one-sided clay-pasteboard liner (180 g/m2).

The PVC offers a high dimensional stability.

Especially designed for short-term window decoration.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and ecosolvent based ink-jet printer.

## **Shelf Life**

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Suitable for use with:









Film:	Monomeric, electrostatic PVC, (cling-film)	
Thickness:	150 mic ±5%	
Adhesive:	N/A	
Adhesion:	N/A	
Liner:	One-sided clay- pasteboard (180 g/m2)	
Application Temperature	+10 - +40 °C	
Temperature Durabil- ity	-40 - +80 °C	
Outdoor Durability	6 months (unprinted film).	

Order Code	W (mm)	L (mm)	Thickness (ums)
INV214339	1370	50	150

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.