

TECHNICAL SPECIFICATIONS

VISTAFLEX® SCB510 PREMIUM FRONTLIT PVC BANNER BLACK BACK 510G/M2

Features & Benefits

- Superior strength product
- Black back provides additional opacity
- Available up to 3.2m and 5m widths
- Applications: Short to mid-term indoor and outdoor banners and flex face signs

Printing

- The material should reach room temperature and a relative humidity of approx. 50% prior to printing.
- Ensure the material is kept free of dust, dirt and static. We recommend using gloves when handling the material.
- Conduct a print test prior to printing the material for a live project.
- 3.2m rolls and above are wound Print Side In (PSI).
- Suitable for printing with Solvent, Eco-Solvent, Latex and UV-C printers.

Storage

- We recommend storing the material in its original tube and wrapping when not in use.
- Material can be stored for up to 2 years when stored in the original packaging
- Store between 20°C and 25°C at 50% relative humidity

Laminating

- This material does not require lamination. However, should the user decide to apply liquid laminate, it is their responsibility to test.



Characteristic	Result
Total Weight	510g/m2
Thickness	370mic ±10
Tensile Strength	
Warp	2140 N/50mm
Weft	2010 N/50mm
Tear Resistance	
Warp	318 N/50mm
Weft	300 N/50mm
Fire Certification	B1
Peeling Strength	60 N/50mm

Product Code	Width (mm)	Length (m)
ISB276236	3200	65
ISB276239	5000	65

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.